

ZIBO JINGGAN REFRACTORY IMPORT AND EXPORT CO.,LTD

Address:NO. 3, Yanhe Road, Boshan, Zibo, Shandong, China
Email:wp@cnjingganrefractory.com/sdwenping@163.com
Contact:Rose Tel/Wechat:+86-13275332819
Tel:86-533-4188518 Fax:86-533-4188518

Graphite Crucible



1, Main technical parameters of Graphite Crucible

ITEM	UNIT	TECHNCIAL INDEX
Density	g/cm ³	1.82-1.85
Shore hardness	HSD	65
Resistivity	$\mu\Omega \cdot m$	11-13
Flexural strength	Mpa	51
Modulus of elasticity	Gpa	11
Compressive strength	Mpa	115
Ash	ppm	500
Porosity	%	12
Particle size	μm	8-10

2,Brief introduction:

Graphite Crucible is made of micron graphite powder as the main raw material and has good thermal conductivity and high temperature resistance. In the application process, the thermal expansion coefficient of the product is small, which has good strain resistance to sudden cool or sudden heat, strong corrosion resistance to acid and alkali, and good chemical stability.

3, Application: widely used in alloy steel smelting and non-ferrous metal smelting

4, Product features:

- 1) Good thermal stability
- 2) Good corrosion resistance, impact resistance
- 3) Good acid and alkali resistance

ZIBO JINGGAN REFRACTORY IMPORT AND EXPORT CO.,LTD

4) Good heat conduction performance

5) Low ash content ensures that precious metals will not be polluted in smelting

5, Specification:80#,100#,120#,150#,200#,250#,300#.....2600#.

6,Good feedback of product use effect,the products have been exported to South Korea, Russia,Pakistan

7,We are a professional supplier, who can provide customers with free product technology, use and other issues

Do you want to find a professional supplier of refractory products?

Do you want to find a professional supplier of graphite electrodes?

Do you want to find a stable and credible supplier?

Then let's contact with jinggan company

Contact me:

Email:wp@cnjingganrefractory.com/sdwenping@163.com

TEL: 86-0533-4188518 / **FAX:** 86-0533-4188518

Rose:+86-13275332819(wechat/whatsapp number)